



AFRICA


www.juntafrica.co.za



Cap

Product Description

- 1) JunT part no. range: T06-xxx
- 2) Grooved fitting
- 3) Sizes 50, 65, 80, 100, 150 mm (2", 2½", 3", 4", 6")
- 4) Ductile iron construction - ASTM A536 GRADE 65-45-12
 - ✓ The properties of Grade 65-45-12 ductile iron are as follows: 65,000 psi (448 MPa) tensile strength, 45,000 psi (310 MPa) yield strength and 12% elongation.
- 5) FM, UL, CE, ISO, CUL CERTIFICATION
- 6) Ethylene Propylene Diene Monomer (EPDM) RUBBER GASKET
- 7) Colours available: Fire Red - RAL-3000, Galvanized
- 8) Pressure rating
 - ✓ Up to 200mm – 20bar static (290PSI / 2000kPA)
 - ✓ 200mm and bigger – 16bar static (232PSI / 1600kPA)



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure Bar/KPA	L mm/in
50 2	60.3 2.375	20.68 2070	26 1.024
65 2 ½	76.1 3	20.68 2070	28 1.102
80 3	88.9 3.5	20.68 2070	28 1.102
100 4	114.3 4.5	20.68 2070	28 1.102
150 6	165.1 6.5	20.68 2070	28 1.102