




AFRICA

www.juntafrica.co.za

Concentric Reducer

Product Description

- 1) **Concentric Reducer (grooved) - PAINTED**
- 2) JunT part no. range: T07-xxx
- 3) Grooved fitting - Manufacturer OEM part no. reference XGQT07 & XGQT11.
- 4) Sizes: 65*50, 80*65, 100*80, 150*100, 200*150 mm (2½*2", 3*2", 4*3", 6*4", 8*6")
- 5) Ductile iron construction - ASTM A536 GRADE 65-45-12
 - ✓ The properties of Grade 65-45-12 ductile iron are as follows: 65,000 psi (448 MPa) tensile strength, 45,000 psi (310 MPa) yield strength and 12% elongation.
- 6) FM, UL, CE, ISO, CUL CERTIFICATION – FM approvals certified to Original Equipment Manufacturers specifications.
- 7) Colours available: Fire Red - RAL-3000
- 8) Pressure rating
 - ✓ Up to 200mm – 20bar static (290PSI / 2000kPa)
 - ✓ 200mm and bigger – 16bar static (232PSI / 1600kPa)



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure Bar/KPA	L mm/in
65x50 2 ½ x 2	76.1x60.3 2.996x2.375	20.68 2070	64 2.62
80x65 3x2 ½	88.9x76.1 3.5x2.996	20.68 2070	64 2.52
100x80 4x3	114.3x88.9 1.5x3.5	20.68 2070	76 2.992
150x100 6x4	168.3x114.3 6.614x4.5	20.68 2070	102 4.016
200x150 8x6	219.1x165.1 8.626x6.5	15.99 1600	127 5