




AFRICA

www.juntafrica.co.za

Equal tee

Product Description



SHORT

- 1) **Equal Tee** – Short radius (S/R) – PAINTED or GALVANISED
- 2) JunT part no. range: T03-xxx or T03-xxxG.
- 3) Grooved fitting – Manufacturer OEM part no. reference XGQT03
- 4) Sizes available: 50, 65, 80, 100, 150, 200, 250mm (2", 2½", 3", 4", 6", 8", 10")
- 5) Ductile iron construction - ASTM A536 GRADE 65-45-12
 - ✓ The properties of Grade 65-45-12 ductile iron are as follows:
65,000 psi (448 MPa) tensile strength, 45,000 psi (310 MPa) yield strength and 12% elongation.
- 6) FM, UL, CE, ISO, CUL CERTIFICATION – FM approvals certified to Original Equipment Manufacturers specifications.
- 7) Colours available: Fire Red - RAL-3000, Galvanized (limited sizes available)
- 8) Pressure rating
 - ✓ Up to 200mm – 20bar static (290PSI / 2000kPa)
 - ✓ 200mm and bigger – 16bar static (232PSI / 1600kPa)

Nominal Size mm/in	Pipe O.D mm/in	Working Pressure Bar/KPA	L mm/in
			Short
50 2	60.3 2.375	20.68 2070	70 2.756
65 2½	76.1 3	20.68 2070	76 2.992
80 3	88.9 3.5	20.68 2070	86 3.386
100 4	114.3 4.5	20.68 2070	102 4.016
150 6	165.1 6.5	20.68 2070	140 5.512
200 8	219.1 8.625	15.99 1600	175 6.890
250 10	273 10.75	15.99 1600	215 8.466