




AFRICA

www.juntafrica.co.za

Reducing Tee

Product Description

- 1) **Reducing Tee – PAINTED**
- 2) JunT part no. range: T04-xxx & T04S-xxx
- 3) Grooved & Threaded fittings - Manufacturer OEM part no. reference XGQT04 / XGQT04S & XGQT08 / XGQT08S.
- 4) Sizes available:
 GROOVED – 80*65, 100*65, 100*80, 150*100 mm (3*2 ½", 4*2 ½", 4*3", 6*4")
 THREADED - 65*40mm (2 ½*1 ½")
- 5) Ductile iron construction - ASTM A536 GRADE 65-45-12
 - ✓ The properties of Grade 65-45-12 ductile iron are as follows: 65,000 psi (448 MPa) tensile strength, 45,000 psi (310 MPa) yield strength and 12% elongation.
- 6) FM, UL, CE, ISO, CUL CERTIFICATION – FM approvals certified to Original Equipment Manufacturers specifications.
- 7) Colours available: Fire Red - RAL-3000
- 8) Pressure rating
 - ✓ Up to 200mm – 20bar static (290PSI / 2000kPa)
 - ✓ 200mm and bigger – 16bar static (232PSI / 1600kPa)



GROOVED FITTING

Nominal Size mm/in	Pipe O.D mm/in	Working Pressure Bar/KPA	L mm/in
80 x 65 3 x 2½	88.9 x 76.1 3.5 x 2.996	20.68 2070	86 3.386
100 x 65 4 x 2½	114.3 x 76.1 4.5 x 2.996	20.68 2070	102 4.016
100 x 80 4 x 3	114 x 88.9 4.3 x 3.5	20.68 2070	102 4.016
150 x 100 6 x 4	165.1 x 114.3 6.5 x 4.5	20.68 2070	140 5.512

THREADED FITTING

Nominal Size mm/in	Pipe O.D mm/in	Working Pressure Bar/KPA	L mm/in
© Copyright JunT Africa 2022			